

**DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

**Ronseal Promise, if you do exactly what it says on the tin,  
this product will do exactly what it says on the tin.**

## **Ronseal One Coat Cupboard Paint transforms kitchen units and cupboards creating a super smooth and long lasting finish.**

**USAGE** • Ideal for use on kitchen units, cupboards, drawers, bedroom furniture, shelving and interior doors. • Transforms melamine, MDF, plywood and chipboard. • Not recommended for worktops or exterior surfaces.

**PREPARATION** • Surfaces should be clean, dry and free from dust, dirt and grease. • Sand surfaces well with 240 grit sandpaper. • Wipe down with white spirit using a lint free cloth.

**APPLICATION** • Stir well. Apply with a bristle brush. • Brush out well and finish in one direction. • A second coat may be required if painting over a very dark colour with a light top coat or when applying a light colour to an extremely porous substrate, i.e. MDF or chipboard. Allow 16 hours between coats.

**COVERAGE AND DRY TIMES** • 8m<sup>2</sup> per litre. • Touch dry in 1-2 hours. • Overcoat after 16 hours if required. • Low temperature, high humidity or poor ventilation may extend drying and recoat times.

**CLEAN UP** • Remove as much product as possible from application equipment prior to cleaning. • Clean brushes with brush cleaner or white spirit.

**CARE AND MAINTENANCE** • Clean surfaces with a detergent solution. • Avoid abrasive cleaners.



**Super Smooth  
Dry in 1-2 Hours**



**One Coat  
No Primer Required**



**Ultra Tough  
and Durable**

**For further advice please contact:**

Ronseal Technical Services Tel: 0114 240 9469

Ronseal Ltd. Chapeltown, Sheffield, S35 2YP.

Tel: 0114 246 7171 Fax: 0114 245 5629

enquiry@ronseal.co.uk

[www.ronseal.co.uk](http://www.ronseal.co.uk)

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company. © Ronseal 2010

**RONSEAL ONE COAT CUPBOARD & MDF PAINT**


Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction. Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed seek medical advice immediately and show this container label. Use only in well ventilated areas. Dispose of this material and it's container to hazardous or special waste collection point.

**WISE PRECAUTIONS** Always read the instructions carefully before use. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal or dispensing of waste coatings. To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat. A/I):

600g/l (2007) / 500g/l (2010).

This product contains a maximum of 445g/l VOC.



**750ml**