

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

The toughest, most durable interior wood paint providing a longer lasting, non yellowing finish.

Ronseal Diamond Hard Wood Paint

Through technological innovation Ronseal have developed an exceptionally tough paint for interior wood. Its advanced polyurethane - acrylic formula delivers a finish that is up to twice as hard as traditional gloss paints. The tough, scratch resistant finish, is guaranteed to provide longer lasting protection, resisting chipping, flaking and peeling. The stay-white formula also prevents the yellowing effect that other interior paints can develop over time, to keep painted surfaces looking good for longer.

Projects can also be completed quickly, as it is touch dry in 1-2 hours, can be recoated in only 4 hours, and has a low offensive odour. It is self-undercoating adhering to all previously painted surfaces, although a primer is required for bare wood. For best results prime with Ronseal Knot Blocking Wood Primer & Undercoat. Ronseal Diamond Hard Wood Paint is drip resistant, and is highly pigmented to provide excellent coverage. It is dirt resistant and will leave an easy to wipe clean finish, that will look like new for longer.

For Best Results	Prime with Ronseal Knot Block Wood Primer & Undercoat to guarantee topcoat performance.
Usage Areas	Specially developed for any interior wooden surface that is subject to heavy wear and tear.
Compatibility	Suitable for use on interior, primed or previously painted wood.
Coverage (750ml)	1 door with 2 coats (up to 10m ²).
Dry Times	Touch dry in 1-2 hours. Recoat in 4 hours.
Clean Up	Brushes wash out in water and detergent.

Ronseal Guarantee

Ronseal will refund the original retail price if paint shows signs of yellowing or excessive wear to the finish after being applied to wood primed using Ronseal Knot Block Primer & Undercoat or to previously painted wood in good condition. Ronseal Diamond Hard Wood Paint should be applied in accordance with the instructions on the tin. Any failure caused by the breakdown of the previous coating is not covered by this guarantee. Proof of purchase is required. This does not affect your statutory rights.

Preparation

Make sure the wood surface to be painted is clean, dry and free from dirt, dust and grease. **Bare Wood:** Lightly sand to remove any loose fibres and wipe clean. Fill in any small holes or surface defects with Ronseal Multipurpose Wood Filler, then apply an appropriate wood primer such as Ronseal Knot Block Wood Primer & Undercoat. **Previously Painted Wood:** Sand down to remove any flaking or blistered paint or varnish. Paintwork that is in sound condition should be sanded first to provide a key. Ensure the wood is clean by wiping with white spirit to remove any dust. Avoid inhalation of dust, wear a suitable face mask when sanding. **Unsound Wood:** Use Ronseal High Performance Wood Filler to repair any damaged areas and replace any rotten wood with sound timber, then treat as bare wood.

Application & Clean Up

Stir well before use. Apply 2 coats evenly with a synthetic brush, finishing in the direction of the grain. Touch dry in 1-2 hours and apply second coat after 4 hours, in normal conditions (dry time and recoat time will be extended with low temperatures and humidity). 750ml of Ronseal Diamond Hard Wood Paint will cover approximately 10m² of wood when applying two coats. Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with water and detergent. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal of paint waste.

RONSEAL DIAMOND HARD WOOD PAINT

Use only in well ventilated areas. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Keep out of reach of children. Protect from frost – do not apply at temperatures below 10°C or in high humidity.

WISE PRECAUTIONS

Always read the instructions carefully before use. Wear suitable clothing and protective gloves. Do not apply if air or surface temperatures are below 10°C (50°F). To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat A/d): 130g/l (2010). This product contains max 90g/l VOC.

For further advice please contact:

Ronseal Technical Services,

Tel: 0114 240 9469

Ronseal Ltd., Chapeltown,

Sheffield S35 2YP

Tel: 0114 246 7171

Fax: 0114 245 5629

E-mail:
enquiry@ronseal.co.uk

www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010



750ml e

