

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.

The ultimate protection and perfect finish for wooden and concrete floors.

Ronseal Perfect Finish Diamond Hard Floor Paint

Ronseal uses advanced acrylic technology to deliver the ultimate paint protection for all wood and concrete floors. Combined with Ronseal's Perfect Finish Floor Pad, it delivers the quickest and easiest way to achieve a long lasting, hard-wearing finish for interior floors. The Perfect Finish Floor Pad applies the optimum amount of paint and the unique foam-flock combination delivers a smooth, even application for a perfect finish. Ronseal Perfect Finish Diamond Hard Floor Paint has a unique formula that is not only knock, scuff and scratch resistant but also provides a superb protective barrier against household chemicals, including oil, detergent, bleach, alcohol, grease and dirt.

Advanced technology: The advanced formula adheres superbly, with a long lasting, super smooth and quick drying finish. It resists flaking, peeling and chipping, maintaining its appearance for longer than standard floor paints.

Usage Areas	Use on wooden, concrete and stone floors including those in kitchens and bathrooms and areas of the highest foot traffic.
Compatibility	Suitable for use over most hard and soft woods, hardboard, chipboard, wood composite, and previously painted surfaces. Do not use over laminate floors, pre-finished floors or ceramic tiles.
Coverage	Up to 30m ² per 2.5L enough for 2 coats on a floor measuring 15m ² .
Dry Times	Touch dry in 1-2 hours. Overcoatable and suitable for light traffic in 4-6 hours.
Clean Up	Brushes wash out in water and detergent.

Preparation

It is not recommended to apply this product in damp conditions or if temperature is below 10°C.

Bare Surfaces: Concrete, brick or stone Allow newly laid concrete to cure for at least 1 month. Thoroughly wire brush the surface and remove dust. Seal with a first coat of Diamond Hard Floor Paint diluted with 10% water or with a coat of a proprietary stabilising solution. **Bare Wood:** Sand with 120 grit paper and remove any sanding dust, grease, oil or dirt with white spirit. Seal any knots and hardwood timbers with a shellac based sealer i.e. knotting solution.

Previously Painted Surfaces: Concrete, brick or stone Thoroughly wire brush to remove any loose or flaking paint. Sand down and wipe clean with white spirit to remove dust. Treat any areas of bare surface as above. **Wood** Remove loose or flaking paint then sand thoroughly and wipe clean with white spirit. Treat any areas of bare surface as above. Avoid inhalation of dust, wear a suitable face mask when sanding.

Application

- 1 Remove overlap and assemble the Perfect Finish Floor Pad, vacuum pad prior to use to remove any loose fibres. Remove the lid which can be used as a tray for loading the pad. If using the lid, put paper down before placing it on the floor as some product may collect on the base of the tray during transit. Stir the paint thoroughly before use.
- 2 Dip the pad evenly into the paint, ensuring the flock is covered.
- 3 Starting in the corner of the room furthest from the door, pull the Perfect Finish Floor Pad towards you. The Perfect Finish Floor Pad holds more paint than a brush so you will be able to apply the Floor Paint in long, smooth strokes before needing to reload.
- 4 When you get near to the other side of the room, turn around and apply in the opposite direction, feathering in to meet coated areas. If coating floorboards, work along 2 floorboards at a time, in the direction of the woodgrain.
- 5 Apply a minimum of 2 coats, allowing 4-6 hours between coats. The floor is ready to walk on after 4-6 hours but allow 72 hours before subjecting to heavy traffic.
- 6 If additional paint is required, Ronseal Diamond Hard Floor Paint is also available in 750ml, 2.5 litre and 5 litre tins.

Clean Up

Remove as much paint as possible from the pad and tray before cleaning. Clean pad and tray whilst wet with water and detergent. Always leave the pad to dry with the flock facing upwards. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

RONSEAL PERFECT FINISH DIAMOND HARD FLOOR PAINT

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Use only in well-ventilated areas. Protect from frost – do not apply below 10°C or in high humidity.

WISE PRECAUTIONS

Always test on a small area first to ensure colour suitability. Use product only as directed. Apply in accordance with the coverage guidelines otherwise product performance will be reduced. Poor ventilation, low temperatures and high humidity will lengthen dry times. Do not cover with carpets or rugs and protect from water and excessive wear and tear for 2-3 days.



EU limit value for this product
(cat A/i): 140g/l (2007/
140g/l (2010). This product
contains max 95g/l VOC.



2.5 Litres e

For further advice please
contact: **Ronseal Technical
Services, Tel: 0114 240 9469**

Ronseal Ltd., Chapeltown,
Sheffield S35 2YP
Tel: 0114 246 7171,
Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What It Says
on the Tin are registered trademarks of The
Sherwin-Williams Company. © 2010