

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™**

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

- **Unique combination of resins and wax polymers provides Diamond Hard protection and a subtle wax finish**
- **As tough and as durable as a floor varnish - can be used in areas of high foot traffic**
- **Water resistant - ideal for use in kitchens and bathrooms**
- **Alternative finish to standard floor varnish - can be used over previously varnished floors**
- **Beautiful, natural, matt wax finish highlights the natural beauty of the wood**
- **Fast dry time - touch dry in 30 minutes, recoat in 2 hours**
- **Low odour • Easy clean up**

WHERE CAN I USE IT?

Ronseal Diamond Hard Floor Wax is ideal for use on wooden floors in high traffic areas and areas where it may eventually come into contact with water such as kitchens and bathrooms. Not suitable for laminate floors.

WHAT SORT OF FINISH?

It produces a beautiful, subtle natural matt wax finish, that allows the grain to show through. For best results, and a true representation of colour, use on bare wood.

HOW MANY COATS?

We advise that a minimum of 3 coats are applied to ensure maximum durability and if required, further coats may be applied, leaving 2 hours between each coat.

COVERAGE:

2.5 litres is normally sufficient to cover 40-50 square metres. This tin should provide enough for 3 coats on a floor measuring 3 metres by 5 metres. Coverage varies with the absorbency and type of wood.

DRY TIME:

Allow 30 minutes for each coat to dry and 2 hours between coats.

PREPARATION:

Varnished floors: Thoroughly sand with 120 grade abrasive paper to provide a key for the wax to adhere to. Wipe over with white spirit to remove dust and allow to dry. Varnish in poor condition should be completely removed.

Unvarnished floors: All existing coatings must be removed and the surface sanded back to a smooth finish. The quickest option is to hire a sanding machine from a tool hire shop. Follow the hire instructions, always test sanding, remembering to sand along the grain. Use a small electric sander or sand by hand to finish off around edges. Do not use an abrasive paper finer than 120 grade. Fill any holes or surface imperfections with Ronseal Multi Purpose Woodfiller. Allow dust to settle then vacuum. Wipe over with white spirit and allow to dry thoroughly. Avoid the inhalation of dust, wear a suitable face mask when sanding.

Unique Protection & Finish



**SCUFF & SCRATCH
RESISTANT**



**BEAUTIFUL
MATT WAX FINISH**

APPLICATION:

Stir thoroughly before and during use. Apply in a warm well ventilated room. Using a wide brush apply the wax evenly and finish in the direction of the wood grain. For best results apply to 3-4 floor boards at a time to avoid overlaps. Apply 3 coats leaving 2 hours between coats. Do not over-brush as this will spread the finish too thinly and affect performance. Before the final coat, lightly rub down with 240 grade abrasive paper and wipe over with a damp cloth then allow to dry. Do not use wire wool. The floor is ready to walk on after 8 hours but allow 72 hours before subjecting to heavy foot traffic.

CLEAN UP:

Clean brushes whilst wet with water and detergent. Remove as much product as possible from the brush before cleaning. Do not empty into drains and watercourses. Some local authorities have special facilities for disposing of waste coatings.

Wipe the tin and lid rim with a clean cloth prior to resealing the pack.

IMPORTANT:

Do not cover with carpets or rugs for 8 days. Protect from water for 5 days. Poor ventilation, low temperatures and high humidity will lengthen recoat and dry times. Colour label indicates approximate colour only. Always test a small inconspicuous area first. Apply in accordance with the coverage guidelines, otherwise product performance will be reduced.

RONSEAL DIAMOND HARD FLOOR WAX

Keep out of the reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas. Protect from frost - do not apply at temperatures below 10°C or in high humidity. To avoid the risk of spillage always store and transport in a secure and upright position.

EU limit value for this product (cat A/I):
140g/l (2007) / 140g/l (2010).
This product contains max 100g/l VOC.

**For further advice please contact:
Ronseal Technical Services, Tel: 0114 240 9469**

Ronseal Ltd, Thorncliffe Park,
Chapeltown, Sheffield, S35 2YP

Tel: 0114 246 7171 Fax: 0114 245 5629

Email: enquiry@ronseal.co.uk

www.ronseal.co.uk

Ronseal and Ronseal Does
Exactly What it Says on the Tin
are registered trade marks of
The Sherwin-Williams Company.
© Ronseal Ltd 2010



2.5Le

