

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™**

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

The ultimate paint protection for all concrete and stone garage floors.

Ronseal Diamond Hard Garage Floor Paint

Ronseal uses advanced acrylic technology to deliver the ultimate paint protection for all concrete and stone garage floors. The unique Diamond Hard formula not only resists knocks, scuffs and scratches but also creates a superb barrier against oil spills, grease, dirt and is resistant to hot tyre pick up. Ronseal's hard-wearing Garage Floor Paint is slip resistant and completely seals concrete dust, leaving an easy clean, tough and long lasting finish.

Advanced Technology: The advanced quick drying formula doesn't require a separate primer, adheres superbly and resists flaking, peeling and chipping, maintaining its appearance for longer than standard garage floor paints.

Usage Areas	Use on concrete or stone garage floors. It is particularly suited for areas of the highest foot traffic.
Compatibility	Suitable for use on concrete or stone and previously painted surfaces.
No. of Coats	A minimum of 2 coats should be applied to ensure maximum durability.
Coverage	Up to 30m ² per 2.5L enough for 2 coats on a garage floor measuring 15m ² .
Dry Times	Touch dry in 1-2 hours. Overcoatable and suitable for light traffic in 4-6 hours.
Clean Up	Brushes wash out in water and detergent.

Preparation

It is not recommended to apply this product in damp conditions or if temperature is below 10°C. Surfaces should be clean and free from oil and grease contamination. Use an oil spot cleaner like Thompson's Oil & Drive Cleaner to remove any oil stains.

Bare Surfaces:

Concrete, Brick or Stone Allow newly laid concrete to cure for at least 1 month. Thoroughly wire brush the surface and remove dust. Seal with a first coat of Diamond Hard Garage Floor Paint diluted with 10% water or with a coat of a proprietary stabilising solution.

Previously Painted Surfaces: Thoroughly wire brush to remove any loose or flaking paint. Sand down and wipe clean with white spirit to remove dust. Treat any areas of bare surface as above.

Application & Clean Up

Stir the paint thoroughly before use. Apply by brush, roller or pad. When using more than one tin, intermix before use to ensure an even colour. Apply a minimum of 2 coats, allowing 4-6 hours between coats. The floor is ready to walk on after 4-6 hours but allow 72 hours before subjecting to heavy foot traffic or vehicles. Remove as much paint as possible from application equipment before cleaning. Clean brushes with water and detergent. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

RONSEAL DIAMOND HARD GARAGE FLOOR PAINT

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Use only in well-ventilated areas. Protect from frost – do not apply below 10°C or in high humidity.

WISE PRECAUTIONS Always test on a small area first to ensure colour suitability. Use product only as directed. Apply in accordance with the coverage guidelines otherwise product performance will be reduced. Poor ventilation, low temperatures and high humidity will lengthen dry times. Protect from vehicles, water and excessive wear and tear for 2-3 days.

EU limit value for this product (cat A/i): 140g/l (2007)/ 140g/l (2010). This product contains max 95g/l VOC.

**For further advice please
contact: Ronseal Technical
Services, Tel: 0114 240 9469**

Ronseal Ltd., Chapelton,
Sheffield S35 2YP
Tel: 0114 246 7171,
Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010



2.5 Litres e

