

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.

- Ultimate protection for doors, skirting, tables, furniture and any interior wood
- Advanced polyurethane formula gives superior resistance to scratches, heat and water
- Beautiful, rich, long-lasting colour
- Touch dry in 30 minutes - recoat in 2 hours
- Low odour & brushes wash out in water

WHERE CAN I USE IT? Any bare or previously treated wood you wish to provide with the ultimate colour and protection. It is ideal for interior doors, skirting boards, table tops and wooden furniture. It is also suitable for use in kitchens and bathrooms.

For wooden floors use Ronseal Diamond Hard Coloured Floor Varnish.

WHAT SORT OF FINISH? Ronseal Diamond Hard Coloured Varnish brings out the inherent beauty of wood, enhancing the natural wood grain providing a beautiful gloss finish.

HOW MANY COATS? 2 coats are normally enough, but untreated wood may need 3 coats for ultimate protection.

DRY TIMES: Allow 30 minutes for each coat to dry and 2 hours between coats.

COVERAGE: This can is normally sufficient for treating 3 door sides with 2 coats (approx 6 sqm).

PREPARATION: Ensure all surfaces are free from wax, grease and oil by wiping with a cloth dampened with white spirit. **Bare Wood:** Sand smooth with fine sandpaper. Do not use steel wool. Remove dust with a damp cloth. **Varnished Wood:** Remove any unsound varnish. Sand well with medium sandpaper to a uniform appearance, and clean with white spirit. Avoid inhalation of dust, wear a suitable face mask when sanding. Allow to dry thoroughly.

APPLICATION: For best results, stir thoroughly before and during use. Apply in a warm, well ventilated room. Using a synthetic filament brush apply 2 or 3 coats. Brush out evenly and finish each coat in the direction of the grain. Leave 2 hours between coats. Before final coat lightly rub down using fine sandpaper and then wipe with a damp cloth.

CLEAN UP: Remove as much varnish from brush as possible before cleaning with water and detergent.

Ultimate
protection



SCRATCH RESISTANT



HEAT RESISTANT



WATER RESISTANT

IMPORTANT: Colour label indicates approximate colour only. Test on a small inconspicuous area for colour suitability. If water is accidentally splashed onto surface within 2-3 days of application, simply remove by gentle wiping with a soft cloth. Do not rub wet surface. Solvent-based polyurethane varnishes should be allowed to age at least 1 month before overcoating with Ronseal Diamond Hard Varnish. Poor ventilation, low temperatures and high humidity will lengthen dry and recoat times. Special precautions may be required when treating pre 1960's painted surfaces. For further advice contact Ronseal Technical Services. Some local authorities have special facilities for disposing of waste coatings. Do not empty product into drains or watercourses.

RONSEAL DIAMOND HARD COLOURED VARNISH

Keep out of the reach of children. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well-ventilated areas. Protect from frost - do not apply below 10°C or in high humidity. To avoid the risk of spillage, always store and transport in a secure and upright position.

For further advice
please contact

Ronseal Technical Services,
Tel: 0114 240 9469

Ronseal Ltd., Chapelton,
Sheffield, S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629

E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does Exactly
What it Says on the Tin are
registered trade marks
of The Sherwin-Williams
Company © 2010



Made in Great Britain

750 ml e