

**IT DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

## Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

- Superb protection for all types of timber decking
- Extremely durable - unique scuff resistant formula
- Contains a biocide to preserve the coating against mould and algae growth
- Fade resistant to sun's harmful UV rays
- Excellent waterproofing barrier
- Resists greying
- Outstanding drying time - deck in use within 24 hours

### What is Ronseal Decking Oil?

Ronseal Decking Oil provides timber decking with a light natural tint, retaining the beauty of the wood to show through. It is specially designed to be used on quality timber decking, to help prevent drying and splitting. It provides a protective barrier against water penetration where constant weathering can cause swelling and warping. Not only does Ronseal Decking Oil enhance your decks beauty and provide superb protection, it also allows your deck to be in use within 24 hours.

### Where can Ronseal Decking Oil be used?

Ronseal Decking Oil will waterproof and protect any hardwood or softwood decking timber including pre-treated, pressure treated or preservative impregnated timber.

#### DIRECTIONS FOR USE

NB: Only specially pre-treated, pressure treated or preservative impregnated timber should be used to build decking. Always test an unobtrusive area before starting general application of Ronseal Decking Oil to ensure desired result is achieved.

#### PREPARATION

Decking timber should be free from dust, dirt, oil, mildew, algae and other contaminants. Some pre-treatments may affect adhesion of decking products. Test by splashing water on timber, if beading occurs, allow a period of weathering and re-test prior to application. Treatment of a small inconspicuous test area to determine colour and adhesion is strongly recommended. For best results, clean surface with Ronseal Decking Cleaner before application and allow to dry thoroughly. All previous coatings must be completely removed before applying Ronseal Decking Oil. Final finish may differ to pack representation due to colour, texture and porosity of the wood.

#### APPLICATION

Do not apply in wet conditions or if rain or frost is likely before product is dry.

1. Important: Decking boards should be completely dry before application.
2. Shake Ronseal Decking Oil thoroughly before pouring into a suitable metal or plastic container. Stir before and during use. Do not dilute.
3. Apply a "flood" coat of Ronseal Decking Oil using a good quality bristle brush or roller.
4. Apply a second coat using the same method. Allow 6 hours between coats. (number of coats required will depend on timber type and absorbency).

#### DRYING TIME

Ronseal Decking Oil can be recoated in 6 hours. The deck will be ready for general use after 24 hours. Drying time will vary depending on climate conditions and porosity of the timber.

#### COVERAGE

This 2.5 litre pack is normally sufficient to coat a deck 10-12m<sup>2</sup> with 2 coats of Decking Oil. Coverage will vary with absorbency of timber and profile of deck.

#### CLEAN UP

Clean all brushes using white spirit or paint brush cleaner immediately. Remove as much product as possible from application equipment before cleaning. Some local authorities have special facilities for disposing of waste products. Do not empty into drains or watercourses.

#### MAINTENANCE

Decking treated with Ronseal Decking Oil can be cleaned using Ronseal Decking Cleaner. The coating should be inspected on a 6 monthly basis. Re-coat as appropriate.

**RONSEAL DECKING OIL** Flammable. Harmful to aquatic organisms, may cause long-term adverse effect in the aquatic environment. MIXTURE EC INDEX 607-176-00-3; dryness or cracking.

Contains alpha-3-(3-(2H-BENZOTRIAZOL... MIXTURE EC INDEX 607-176-00-3; 3,bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; COBALT CARBOXYLATE;ETHYL METHYL KETOXIME. May produce an allergic reaction.

Keep out of reach of children. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well-ventilated areas. Dispose of this material and its container to hazardous or special waste collection point.

After contact with skin, wash immediately with plenty of water. This material and its container must be disposed of in a safe way. Wear suitable gloves. If swallowed seek medical advice immediately and show this container label. To avoid the risk of spillage, always store and transport in a secure and upright position.

**For further advice  
please contact:  
Ronseal Technical  
Services, Tel: 0114 240 9469**

Ronseal Ltd. Thorncliffe Park,  
Chapeltown, Sheffield. S35 2YP  
Tel: 0114 246 7171 Fax: 0114 245 5629  
enquiry@ronseal.co.uk

[www.ronseal.co.uk](http://www.ronseal.co.uk)

**2.5 litre** e



RONSEAL AND RONSEAL DOES EXACTLY WHAT IT SAYS ON THE TIN ARE REGISTERED TRADEMARKS OF THE SHERWIN-WILLIAMS COMPANY © 2010. MADE IN UK

