

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

- **Hardwearing, scuff resistant formula withstands foot traffic**
- **Ultra tough and durable stain resists cracking, peeling and blistering**
- **Quick drying - Rainproof in 90 minutes**
- **Outperforms conventional Woodstains or Varnish on outdoor decking**
- **Natural Matt finish**

What is Ronseal Decking Stain?

Ronseal Decking Stain is the ultimate in one step colour, protection and waterproofing for decking. Its superior formula provides a tough and durable finish for decking, subject to foot traffic, and is rainproof in just 90 minutes. Ronseal Decking Stain will outperform any conventional Woodstain or Varnish on decking. Available in a range of classic colours, Ronseal Decking Stain is all you need to colour and protect decking.

Where should it be Used?

Ronseal Decking Stain is specially formulated for use on all decking timber including pre-treated, pressure treated and preservative impregnated wood. Ronseal Decking Stain is recommended for all exterior horizontal timber where foot traffic and wear will occur. It can be used on new, or decking timber that has been previously stained or weathered.

PREPARATION

NB: Only specially pre-treated, pressure treated, or preservative impregnated timber should be used to build decking. Use Ronseal Decking Cleaner to remove any dust, dirt, grease, oil, mildew, algae and other contaminants. Remove any existing loose, flaking or peeling coatings.

New decking timbers need to be thoroughly prepared before treatment with Ronseal Decking Stain. Apply Ronseal Decking Cleaner and scrub vigorously with a stiff brush to open the pores of the wood and to remove any contamination remaining from the manufacture of the decking. Rinse thoroughly with clean water, ideally using a pressure washer and allow to dry.

Test effectiveness of cleaning by spraying the deck with water. If beading occurs, re-clean. Retest prior to application of Ronseal Decking Stain.

APPLICATION

The treatment of a small test area to determine final colour is recommended. Colour may be influenced by texture, grain, colour, porosity, type of wood and previous treatment. Colour label indicates approximate colour only. Do not apply in wet conditions, if rain or frost is likely before product is dry, or if temperature is below 10°C.

1. Stir thoroughly before and during use, do not dilute.
2. Apply using a good quality wide brush designed for the application of water-based finishes, or a synthetic or lambswool roller.

3. Apply product liberally to ensure even penetration and complete coverage of the decking is achieved. When roller the product always back brush to ensure coverage is uniform.
4. When applying to deck boards; treat 3-4 boards at a time to avoid lap marks. Ensure the leading edge is distributed evenly. Always work along the grain. For maximum protection apply to all sides and ends of the decking prior to construction.
5. Two coats are recommended allowing 4 hours between coats. A third coat may be applied if a deeper colour is required.

DRYING TIME

Drying time will vary depending on climatic conditions and substrate. Generally the coating will be rainproof in 90 minutes and ready to recoat in 4 hours. Allow 24 hours before subjecting the coating to foot traffic.

COVERAGE

This 3 litre pack is normally sufficient to coat:
Rough sawn boards two coats - 15-20 square metres.
Smooth planed boards two coats - 20-25 square metres.
Two coats are recommended. Coverage may be reduced on deeply profiled boards.

CLEAN UP

Clean brushes whilst wet with water and detergents. Wipe the tub and lid rim with a clean cloth prior to resealing the pack. Remove as much product as possible from the brush before cleaning. Do not empty into drains or watercourses. Some local authorities have special facilities for disposing of waste coatings.

MAINTENANCE

Decking treated with Ronseal Decking Stain can be cleaned using Cleaner. The coating should be inspected on an annual basis. Recoat as appropriate.

WISE PRECAUTION

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep out of the reach of children. Use only in well ventilated areas. Protect from frost. Do not use below 10°C or in conditions of high humidity. Ensure container is fully resealed after use.

EU limit value for this product (cat A/E): 130g/l (2010). This product contains max 50g/l VOC.

For further advice please contact: Ronseal Technical Services, Tel: 0114 240 9469

Ronseal Ltd, Thorncroft Park,
Chapeldown, Sheffield, S35 2YP
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk
www.ronseal.co.uk

RONSEAL AND RONSEAL DOES
EXACTLY WHAT IT SAYS ON THE
TIN ARE REGISTERED TRADEMARKS
OF THE SHERWIN-WILLIAMS
COMPANY © 2016. MADE IN UK

3 Litres e

