

**IT DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN™**

**Ronseal Promise, if you do exactly what it says on the tin,  
this product will do exactly what it says on the tin.**

### **NEW FORMULA**

- **Superb waterproofing protection**
- **Protects timber from constant wetting, drying, splitting & swelling.**
- **Resists moisture penetration whilst allowing timber to breathe**
- **Resists mould & algal growth on the surface of the coating**
- **Resists greying**
- **Ideal for spraying**

### **What is Ronseal Decking Protector?**

Ronseal Decking Protector provides the ultimate waterproofing protection for quality decks. Its unique wax enriched formulation will create a superb barrier against water penetration and helps prevent the degradation of your deck, caused by the constant wetting and drying. The quick drying formulation gets your deck back in use quicker than traditional decking protectors. It resists unsightly surface mould and algal growth, and keeps your deck looking good for longer.

### **Where can Ronseal Decking Protector be used?**

Ronseal Decking Protector will waterproof and protect any hardwood or softwood, ridged or smooth decking timber including untreated, pre-treated, pressure treated or preservative impregnated timber.

**NOTE:** Ronseal's Decking Protector's new formulation is unique and should not be applied in conjunction with any other decking protector including those within the Ronseal range. If coating a deck previously treated with Ronseal Decking Protector allow 12 months to weather before applying this new improved formulation.

### **DIRECTIONS FOR USE**

NB: Only specially pre-treated, pressure treated or preservative impregnated timber should be used to build decking. Always test an unobtrusive area before starting general application of Ronseal Decking Protector to ensure desired result is achieved.

### **PREPARATION**

Decking timber should be free from all dust, dirt, oil, mildew, algae and other contaminants. For best results, clean surfaces with Ronseal Decking Cleaner prior to application and allow to dry thoroughly.

It is extremely important that any cleaning residues are completely washed away to maximise the performance of Ronseal Decking Protector. Remove all existing loose, flaking or peeling coatings and ensure the decking is completely dry.

### **APPLICATION**

Do not apply in wet conditions or if rain or frost are likely before product is dry.

1. Shake well before and during use. Pour Ronseal Decking Protector into a suitable plastic container.
2. Apply liberally using brush, roller or low pressure sprayer (for best results ensure temperature is above 10°C).
3. On decking (horizontal timber) remove puddling by redistributing to dry areas after 15 minutes.
4. For maximum protection apply 2 coats. Recoat as soon as first coat is dry (maximum 2 hours). Dry times will vary with climatic conditions and porosity of timber. Allow 24 hours for the protector to dry before subjecting the decking to any foot traffic.  
Note - warm breezy weather will significantly reduce dry times.

5. If recoat times are exceeded the 2nd coat may be repelled by the first coat. Leave for 20 minutes and redistribute product with a dry brush.

### **COVERAGE**

Coverage will vary depending on the porosity of the timber. This 5 litre pack should be sufficient to coat a deck measuring 15-20 square metres with two coats.

### **CLEAN UP**

Clean all application equipment using warm water and detergent immediately. Remove as much product as possible from the application equipment before cleaning. Some local authorities have special facilities for disposing of waste products. Do not empty into drain or watercourses.

### **MAINTENANCE**

Decking treated with Ronseal Decking Protector can be cleaned with Ronseal Decking Cleaner. Allow to dry thoroughly then re-coat with Ronseal Decking Protector. Decking should be inspected on an annual basis and re-coated as appropriate.

### **WISE PRECAUTIONS**

1. Ronseal Decking Protector is not recommended for use on decking that has recently been coated with a product such as Ronseal Decking Stain, but will work well on weathered surfaces if porous enough to allow penetration.
2. Protect adjacent areas such as decorative coatings, plastic and glass from overspray. Any overspray should be removed with a damp cloth whilst wet.
3. Do not spray on vegetation. Protect plants and surrounding grass from overspray.
4. Do not use detergents to clean down substrate to be sealed.

### **RONSEAL DECKING PROTECTOR**

Keep out of reach of children. Avoid contact with the skin and eyes. In case of contact with the eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Use only in well ventilated areas.

EU limit value for this product is (cat A/i): 140g/l (2010). This product contains max 40g/l VOC.



**For further advice please contact:**

**Ronseal Technical Services, Tel: 0114 240 9469**

Ronseal Ltd. Thorncliffe Park,  
Chapelton, Sheffield. S35 2YP  
Tel: 0114 246 7171 Fax: 0114 245 5629  
enquiry@ronseal.co.uk

[www.ronseal.co.uk](http://www.ronseal.co.uk)

RONSEAL AND RONSEAL DOES  
EXACTLY WHAT IT SAYS ON THE  
TIN ARE REGISTERED TRADEMARKS  
OF THE SHERWIN-WILLIAMS  
COMPANY © 2010. MADE IN UK

**5 litre** e

