

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

Ronseal Eco Decking Stain delivers superior performance compared to standard decking stains due to the unique water-borne Linseed Oil based resin system which protects and waterproofs decking from the harmful effects of rain and UV rays whilst resisting cracking, peeling and flaking. Translucent pigments deliver long lasting natural colour which enhance the beauty of wooden decking.

Linseed Oil is a naturally derived plant oil and has been used as a replacement for as much of the crude oil derived materials (petrochemicals) found in conventional decking stains as possible.

Ronseal Eco Decking Stain is packaged in a steel tin which contains up to 40% recycled material and is 100% recyclable.

Ronseal are proud to sponsor the Woodland Trust the UK's leading woodland conservation charity. **25p** from the sale of this tin will be donated to the Woodland Trust to restore 1m² of native UK woodland. For more information on this go to www.ronseal.co.uk/eco

WHERE CAN I USE IT? **Ronseal Eco Decking Stain** is specially formulated for use on all decking timber including pre-treated, pressure treated and preservative impregnated wood. **Ronseal Eco Decking Stain** is recommended for all exterior horizontal timber where foot traffic and wear will occur. It can be used on new, or previously stained and weathered decking.

HOW MANY COATS? We advise that a minimum of 2 coats are applied to ensure maximum durability, and if required, a third coat may be applied leaving 4 hours between each coat.

DRYING TIMES Drying time will vary depending on climatic conditions and substrate. Generally the coating will be rainproof in 90 minutes and ready to recoat in 4 hours. Allow 24 hours before subjecting the coating to foot traffic.

COVERAGE 2.5 litres is normally sufficient to coat 10-15 sq metres on all board types.

PREPARATION NB: Only specially pre-treated, pressure treated, or preservative impregnated timber should be used to build decking. Use **Ronseal Decking Cleaner** to remove any dirt, grease, oil, mildew, algae and other contaminants. Remove any existing loose, flaking or peeling coatings. New decking timbers need to be thoroughly prepared before treatment with **Ronseal Eco Decking Stain**. Apply **Ronseal Decking Cleaner** and scrub vigorously with a stiff brush to open the pores of the wood and to remove any contamination remaining from the manufacture of the decking. Rinse thoroughly with clean water, ideally using a pressure washer and allow to dry. Test effectiveness of cleaning by splashing the deck with water. If beading occurs, re-clean. Retest prior to application of **Ronseal Eco Decking Stain**.

APPLICATION The treatment of a small test area to determine final colour is recommended. Colour may be influenced by texture, grain, colour, porosity, type of wood and previous treatment. Colour label indicates approximate colour only. Do not apply in wet conditions, if rain or frost is likely before product is dry, or if temperature is below 10°C.

**Superior
Colour &
Protection**



UV resistant



Water resistant



Frost resistant

1. Stir thoroughly before and during use, do not dilute.
2. Apply using a good quality wide brush designed for the application of water-based finishes.
3. Apply product liberally to ensure even penetration and complete coverage of the decking is achieved.
4. When applying to deck boards; treat 3-4 boards at a time to avoid lap marks. Ensure the leading edge is distributed evenly. Always work along the grain. For maximum protection apply to all sides and ends of the decking prior to construction.
5. Two coats are recommended allowing 4 hours between coats. A third coat may be applied if a deeper colour is required.

CLEAN UP Remove as much product as possible from the brush before cleaning. Clean brushes whilst wet with water and detergents. Wipe the tub and lid rim with a clean cloth prior to resealing the pack. Do not empty into drains or watercourses. Some local authorities have special facilities for disposing of waste coatings.

MAINTENANCE Decking treated with Ronseal Eco Decking Stain can be cleaned using Ronseal Decking Cleaner. The coating should be inspected on an annual basis. Recoat as appropriate.

RONSEAL ECO DECKING STAIN Avoid contact with skin and eyes. After contact with skin, wash immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep out of the reach of children. Use only in well ventilated areas. Protect from frost. Do not use below 10°C or in conditions of high humidity. To avoid risk of spillage, always store and transport in a secure and upright position.

EU limit value for this product (cat A/I): 140g/l (2007) / 140g/l (2010). This product contains max 70g/l VOC.

**For further advice please contact:
Ronseal Technical Services, Tel: 0114 240 9469**

Ronseal Ltd., Chapeltown, Sheffield S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk www.ronseal.co.uk
The Woodland Trust is a charity registered in England and Wales No.294344 and in Scotland No.SC038885. Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trade marks of The Sherwin-Williams Company. © 2010

2.5 Litres 
Made in Great Britain

