

The easiest way to permanently cover hairline cracks providing the ultimate base for emulsion paint

Ronseal Crack Filling, Flexible Basecoat permanently fills and covers hairline cracks in interior walls and ceilings.

The superior flexible basecoat ensures a longer lasting finish for emulsion topcoats. The specifically developed elastomeric formula stretches and flexes with wall and ceiling movement, expanding and contracting over existing hairline cracks. The super flexible Basecoat absorbs movements in your walls and ceilings, stopping the cracks from reappearing and resisting any further cracks developing.

Ronseal Crack Filling, Flexible Basecoat is the ultimate foundation for your emulsion paint. It both fills and covers hairline cracks and wall imperfections in just one application, leaving an even base for your emulsion topcoat. It is touch dry in 2 hours, and ready to paint in just 4 hours.

PREPARATION

Ensure the wall or ceiling is free of any loose particles or flaking paint. All surfaces should be clean, dry and free from dust, dirt, grease and mould.

If any cracks or holes are larger than a hairline, fill with an appropriate wall filler and leave to dry before sanding down well. Glossy surfaces should be abraded to ensure Basecoat will adhere.

For best results on highly porous surfaces, such as new plaster, it is advised that Ronseal Basecoat is diluted with 20% clean water. This will ensure excellent adhesion over very porous surfaces. Once dry apply a second coat of undiluted Basecoat.

APPLICATION

Stir the product well and load a bristle brush or a short pile emulsion roller with the Basecoat (transfer to a roller tray for easier roller loading).

Apply the Basecoat evenly to the surface, finishing in a vertical direction.

Apply thoroughly ensuring the paint is distributed evenly and into all cracks. Do not roll out too thinly as this will reduce performance.

It should be touch dry in 2 hours and ready to paint in 4 hours.

CLEAN UP

Remove as much product as possible from application equipment before washing. Simply wash the roller or brush in warm soapy water immediately after use. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal of waste coatings.

COVERAGE & DRY TIMES

2.5 litres will cover 12.5-20m². Touch dry in 2 hours, ready for emulsion topcoat in 4 hours. Low temperature, high humidity or poor ventilation may extend drying times.

FOR FURTHER ADVICE PLEASE CONTACT:
RONSEAL TECHNICAL SERVICES,
Tel: 0114 240 9469
Ronseal Ltd, Thomcliffe Park,
Chapelton, Sheffield, S35 2YP
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk www.ronseal.co.uk

RONSEAL AND RONSEAL DOES EXACTLY WHAT IT SAYS ON THE TIN ARE REGISTERED TRADEMARKS OF THE SHERWIN-WILLIAMS COMPANY © 2010. MADE IN UK.



2.5 litre e

C00051

HEALTH & SAFETY

Keep out of the reach of children. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas. Avoid the inhalation of dust, wear a suitable face mask when sanding.

Wise precautions: To avoid risk of spillage, always store and transport in a secure and upright position. Protect from frost. Do not apply below 10°C or in high humidity.

36305



EU limit value for this product (cat A/i): 75 g/l (2007)/30g/l (2010).
This product contains max 4g/l VOC.