

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

- **Deep penetrating formula feeds & nourishes the wood**
- **Natural sheen finish highlights the natural beauty of the wood**
- **Water resistant formulation**
- **Quick drying**

WHERE CAN I USE IT? Ronseal Floor Oil is a high quality floor oil for the protection, maintenance and enhancement of wooden floors. The unique formulation penetrates deep into the wood nourishing and ensuring a wear resistant protective finish. The water resistant formula helps to repel water and resist water marking.

WHAT SORT OF FINISH? Ronseal Floor Oil nourishes the wood to form a natural sheen that warms and enhances the wood.

HOW MANY COATS? 3 coat application.

DRYING TIMES Dry time 30 mins. Recoat 2 hours.

COVERAGE 2.5 litres is normally sufficient to cover 40-60m² with one coat. Dependent on the porosity or species of the wood.

PREPARATION New floors: Sand the floor in the direction of the grain with 120 grit sand paper, either by hand or by machine. Vacuum the floor to remove dirt and dust. Wipe down with white spirit to remove fine dust and allow to dry thoroughly before coating with Ronseal Floor Oil. Use Ronseal Floor Oil as directed. Wear a mask whilst sanding to avoid the inhalation of dust. **Previously Oiled Floors:** Vacuum the floor to remove dirt and dust. Wipe down with white spirit to remove fine dust and any traces of grease. Allow to dry thoroughly before coating with Ronseal Floor Oil. Use Ronseal Floor Oil as directed. Previously varnished floors should be stripped completely and then prepared as new floors.

APPLICATION For ease of application apply Ronseal Floor Oil in sections, normally 3 or 4 floorboards at a time. Apply liberally by lint free cloth or brush. Allow 15 minutes for Ronseal Floor Oil to penetrate into the wooden floor. Lightly remove excess with a lint free cloth and allow to dry. After final coat has dried, buff surface with a lint free cloth to achieve a sheen finish. Repeat until 3 coats have been applied using recommended recoat times.

MAINTENANCE Floors should be maintained with Ronseal Floor Oil when necessary, normally once or twice a year. Floors can also be patch repaired if some areas are showing greater signs of wear. Wipe up spills immediately.

CLEAN UP Remove as much product as possible from application equipment before washing. Clean equipment immediately after use with white spirit or brush cleaner. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

RONSEAL FLOOR OIL Flammable. Harmful to aquatic organisms may cause long term adverse effects in the aquatic environment. Repeated exposure may cause skin cracking or dryness. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Dispose of this material and it's container to hazardous or special waste collection point. Contains ETHYL METHYL KETOXIME. May produce an allergic reaction.

EU limit value for this product (cat A/II): 600g/l (2007) / 500g/l (2010). This product contains max 420g/l VOC.

WARNING Application cloths and soiled rags may self ignite without warning. Dispose safely to avoid fire risks. Wash out well in warm soapy water before disposal.

**For further advice please contact:
Ronseal Technical Services, Tel: 0114 240 9499**

Ronseal Ltd., Chapelton, Sheffield S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trade marks of The Sherwin-Williams Company. © 2010

2.5 Litres 

