

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

- Specifically designed to enhance and protect hardwood decking
- Protects decking from greying effects of UV rays
- Long lasting, waterproofing protection
- Lightly tinted, natural finish
- Easy to apply by brush
- Deck is back in use in 24 hours

Ronseal Hardwood Decking Oil is a superior blend of oils and resins, specifically designed to enhance and protect hardwood decking. It penetrates the wood to replace natural oils lost in the manufacturing process as well as naturally through weathering which can cause wood to crack and split.

Ronseal Hardwood Decking Oil protects the wood from the greying effect of UV rays as well as forming a waterproofing barrier to prevent water damage and discolouration. The long lasting, durable finish resists scuff marks and the slightly tinted finish fully enhances the unique beauty of each hardwood board.

Ronseal Hardwood Decking Oil should only be used on hardwood decks. If you wish to treat softwood decking, we recommend **Ronseal Decking Oil**.

DIRECTIONS FOR USE

Always test an unobtrusive area before starting general application of Ronseal Hardwood Decking Oil to ensure desired result is achieved.

PREPARATION

Decking timber should be free from dust, dirt, oil, mildew, algae and other contaminants. Treatment of a small inconspicuous test area to determine colour and adhesion is strongly recommended. For best results, clean surface with Ronseal Decking Cleaner before application and allow to dry thoroughly. All previous coatings must be completely removed before applying Ronseal Hardwood Decking Oil. Final finish may differ to pack representation due to colour, texture and porosity of the wood.

APPLICATION

- Do not apply in wet conditions or if rain or frost is likely before product is dry.
1. Important: Decking boards should be completely dry before application.
 2. Shake Ronseal Hardwood Decking Oil thoroughly before pouring entire contents into a suitable metal or plastic container. Stir before and during use. Do not dilute.
 3. Apply a "flood" coat of Ronseal Hardwood Decking Oil using a good quality bristle brush.
 4. Apply a second coat using the same method. Allow 6 hours between coats. (number of coats required will depend on timber type and absorbency).

DRYING TIME

Ronseal Hardwood Decking Oil can be recoated in 6 hours. The deck will be ready for general use after 24 hours. Drying time will vary depending on climate conditions and porosity of the timber.

COVERAGE

This 2.5 litre pack is normally sufficient to coat a deck 10-12m² with 2 coats of Ronseal Hardwood Decking Oil. Coverage will vary with absorbency of timber and profile of deck.

CLEAN UP

Clean all brushes using white spirit or paint brush cleaner immediately after use. Remove as much product as possible from application equipment before cleaning. Some local authorities have special facilities for disposing of waste products. Do not empty into drains or watercourses.

MAINTENANCE

Decking treated with Ronseal Hardwood Decking Oil can be cleaned using Ronseal Decking Cleaner. The coating should be inspected on a 6 monthly basis. Re-coat as appropriate.

RONSEAL HARDWOOD DECKING OIL

Flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Wear suitable gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

Dispose of this material and its container to hazardous or special waste collection point.

Contains alpha-3-(3-(2H-BENZOTRIAZOL...MIXTURE EC INDEX 607-176-00-3, bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate, Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME.

May produce an allergic reaction.

EU limit value for this product (cat A/i) 600g/l (2007)/500g/l (2010).
This product contains max 500g/l VOC.

For further advice

please contact:

**Ronseal Technical
Services, Tel: 0114 240 9469**

Ronseal Ltd, Thomcliffe Park,
Chapelton, Sheffield, S35 2YP
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk

www.ronseal.co.uk

2.5 litre e

RONSEAL AND RONSEAL DOES EXACTLY WHAT IT SAYS ON THE TIN
ARE REGISTERED TRADEMARKS OF THE SHERWIN-WILLIAMS COMPANY
© 2010. MADE IN UK

