

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.

Ronseal High Traffic Decking Stain lasts longer than ordinary decking stains.

High Traffic formulation delivers increased protection against foot traffic

Quick drying – Rainproof in 90 minutes

Advanced translucent pigments protect from the greying effects of UV rays

Advanced weather resistant formulation resists cracking and peeling

Ronseal High Traffic Decking Stain's tough high traffic formulation withstands foot traffic for longer than ordinary decking stains prolonging the life and colour of your deck. The tough high performance formulation resists cracking and peeling and the translucent colour pigments deliver long lasting colour that naturally complements and enhances the beauty of your deck. For protection against the elements Ronseal High Traffic Decking Stain provides superior waterproofing protection whilst protecting the wood from the harmful effects of frost and UV rays.

AREAS OF USE:

Ronseal High Traffic Decking Stain can be used on ridged or smooth decking timber including pre-treated, pressure treated and preservative impregnated wood. It is recommended for all exterior horizontal timber where foot traffic and wear will occur. It can be used on new wood, weathered wood or wood which has been previously treated with a similar colour and is in a sound condition.

DRYING TIMES:

Rainproof in 1½ hours, re-coat in 4 hours. Drying times will vary depending on climatic conditions and substrate coated. Allow 24 hours before subjecting the coating to foot traffic.

COVERAGE:

This 2.5L tin will cover 10-15 square metres with 2 coats for all board types. Coverage rates may vary depending on the absorbency and profile of the wood.

PREPARATION:

Only pre-treated, pressure treated or preservative impregnated timber should be used to build decking. Decking timber should be free from all dust, dirt, oil, mildew, algae and other contaminants. Remove any existing loose, flaking or peeling coatings. On pre-treated or wax coated decking timber try a small area for adhesion properties. New timber decks need to be thoroughly prepared before treatment. Apply **Ronseal Decking Cleaner** and scrub vigorously with a stiff brush to open the pores of the wood, this removes any contamination remaining from the manufacturing process. Rinse thoroughly with clean water, ideally using a pressure washer and allow to dry. Test the effectiveness of the cleaning by splashing the deck with water. If beading occurs, re-clean and retest prior to application. Colour label indicates approximate colour only. The treatment of a small test area to determine the final colour is recommended. Colour may be influenced by texture, grain, colour, porosity, type of wood and previous treatments.

All weather
protection



UV
Resistant



Rain
Resistant



Frost
Resistant

APPLICATION:

Stir thoroughly before and during use, do not dilute. Apply using a good quality wide brush designed for the application of water based finishes. Apply product liberally to ensure even penetration and complete coverage of the decking is achieved. Apply to 3-4 boards at a time to avoid lap marks. Ensure the leading edge is distributed evenly. Always work along the grain. For maximum protection apply to all sides and the ends of the decking prior to construction. Two coats are recommended allowing 4 hours between coats. A third coat may be applied if a deeper colour is required.

CLEAN UP:

Remove as much product from the brush before cleaning. Clean brushes whilst wet with warm water and detergents. Wipe the tin and lid rim with a clean cloth prior to resealing the pack. Do not empty into drains or watercourses. Some local authorities have special facilities for disposing of waste coatings.

MAINTENANCE:

Decking treated with Ronseal High Traffic Decking Stain can be cleaned using Ronseal Decking Cleaners. Coatings should be inspected on an annual basis. Recoat as appropriate.

RONSEAL HIGH TRAFFIC DECKING STAIN

Keep out of the reach of children. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas.

Wise precautions: To avoid risk of spillage, always store and transport in a secure and upright position. Protect from frost. Do not apply below 10°C or in high humidity.

EU limit value for this product (cat A/i):140g/l (2010).
This product contains max 55g/l VOC

For further advice please contact:

Ronseal Technical Services, Tel: 0114 240 9469

Ronseal Ltd., Chapelton, Sheffield S35 2YP

Tel: 0114 246 7171, Fax: 0114 245 5629

E-mail: enquiry@ronseal.co.uk

www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trade marks of The Sherwin-Williams Company. © 2010

2.5 Litres 
Made in Great Britain



HIGH TRAFFIC
DECKING STAIN
SHADE LABELS

DARK OAK

CEDAR

TEAK

MEDIUM OAK

NATURAL PINE