

**DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

**Ronseal Promise, if you do exactly what it says on the tin,  
this product will do exactly what it says on the tin.**

## **Advanced formula primes, undercoats and blocks wood knots in one – ensuring a longer lasting knot free topcoat finish.**

### **Ronseal Knot Block Wood Primer & Undercoat**

Through technological innovation Ronseal have developed a breakthrough primer and undercoat with knot blocking technology all in one. Not only does it both prime and undercoat, it permanently stops wood resins from staining through to the topcoat. By creating a barrier that contains and seals knot extractives, the unsightly discolouration of newly painted surfaces is prevented, so improving the longevity of a gloss paint finish.

The unique formula is quick drying and highly pigmented to deliver excellent hiding power. It will adhere superbly to either bare or previously painted wood, making it an excellent basecoat for any topcoat wood finish.

<b>For Best Results</b>	Overcoat with Ronseal Diamond Hard Wood Paint for long lasting topcoat finish.
<b>Usage Areas</b>	Ideal for all smooth planed wood, especially Pine. Also blocks resins in resinous hardwoods such as Mahogany, Oak and Cedar. Ideal for use on any interior wood. (Also suitable for exterior wood).
<b>Compatibility</b>	Suitable for use on all bare woods.
<b>Coverage (750ml)</b>	1 door with 2 coats (up to 10m <sup>2</sup> ).
<b>Dry Times</b>	Touch dry in 2 hours. Overcoat after 6 hours.
<b>Clean Up</b>	Brushes wash out in water and detergent.

### **Ronseal Guarantee**

Ronseal will refund the original retail price if the product fails to block wood knots after being applied to bare wood, when used in conjunction with Ronseal Diamond Hard Wood Paint. Ronseal Knot Block Wood Primer and Undercoat should be applied in accordance with the instructions on the tin. Any failure caused by the breakdown of the previous coating is not covered by this guarantee. Proof of purchase is required. This does not affect your statutory rights.

### **Preparation**

Make sure the wood is clean, dry and free from dirt, dust and grease. **Bare Wood:** Lightly sand to remove any loose fibres and wipe clean. Fill in any small holes or surface defects with Ronseal Multi Purpose Wood Filler. **Previously Painted Wood:** Unsound paint, (i.e. flaking) should be completely removed before a new coat is applied. Paintwork that is in sound condition should be sanded first to provide a key. Ensure the wood is clean by wiping with white spirit to remove any dust. Avoid inhalation of dust, wear a suitable face mask when sanding. **Unsound Wood:** Use Ronseal High Performance Wood Filler to repair any damaged areas and replace any rotten wood with sound timber, then treat as bare wood.

### **Application & Clean Up**

Stir well before use. Apply 2 coats evenly with a synthetic brush, finishing in the direction of the grain. Touch dry in 2 hours and overcoat in 6 hours in normal conditions (dry time and recoat time will be extended with low temperatures and humidity). 750ml of Ronseal Knot Block Wood Primer & Undercoat will cover approx 10m<sup>2</sup> of wood when applying 2 coats. Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with water and detergent. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal of paint waste.

### **RONSEAL KNOT BLOCK WOOD PRIMER & UNDERCOAT**

Use only in well ventilated areas. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Keep out of reach of children.

### **WISE PRECAUTIONS**

Always read the instructions carefully before use. Wear suitable clothing and protective gloves. Protect from frost – do not apply at temperatures below 10°C or in high humidity. To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat A/d): 130g/l (2010).  
This product contains max 78g/l VOC.

**For further advice please  
contact: Ronseal Technical  
Services, Tel: 0114 240 9469**

Ronseal Ltd., Chapeltown,  
Sheffield S35 2YP  
Tel: 0114 246 7171  
Fax: 0114 245 5629  
E-mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
[www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010



**750ml e**