

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN*

Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.

A SMOOTH FINISH FILLER THAT DELIVERS PERFECT RESULTS EVERY TIME

RONSEAL SMOOTH FINISH FILLERS are manufactured utilising fine fillers and resins to provide a smoother consistency for easy application. Once applied these smooth fillers will dry to a uniform finish that is easier to sand producing a smooth surface ready for decorating.

RONSEAL MULTI PURPOSE FILLER is the ultimate, versatile, interior wall filler, providing a strong repair to a variety of damaged surfaces. Ronseal's high performance formula ensures the filler offers excellent adhesion filling gaps up to 20mm deep and provides a long lasting repair that will not shrink or crack when repairing plaster, stone, concrete or wood.

Usage Areas	Developed for use on either plaster, stone, concrete or wood.
Gap Size	Fills gaps up to 20mm deep (15mm on vertical surfaces).
Dry Time	After application, surface is touch dry in 1-2 hours.*
Post Repair	Can be drilled once dried hard.
Clean Up	Remove excess product from tools immediately after use using a damp cloth.

PREPARATION Ensure surface and cracks are clean, dry and free from dust, grease and other contamination. Touch in nails and screw heads with a solvent based paint.

APPLICATION **1** Pack the filler well into area of repair, ensuring the filler is slightly proud of the surface being filled. **2** For deeper repairs above 20mm, build the filler up in layers, ensuring the filler has dried between applications. **3** Smooth over filler with the Ronseal applicator or a wet knife prior to drying. **4** If necessary, sand to a smooth finish once dried hard.

Avoid the inhalation of dust and wear a suitable face mask when sanding.

* Surface dry in approximately 1-2 hours depending on size and depth of hole. Cold and damp conditions may extend dry time.

CLEAN UP To prevent product from drying out, ensure the plastic film is pushed firmly onto the surface of the filler and the lid is tightly closed. Remove excess product from tools prior to cleaning. Tools should be washed in warm water immediately after use. Store away from areas of extreme temperatures and protect from frost.

RONSEAL MULTI PURPOSE FILLER Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Use only in well ventilated areas. Keep out of the reach of children.

**FOR FURTHER ADVICE PLEASE CONTACT:
RONSEAL TECHNICAL SERVICES, Tel: 0114 240 9469**
Ronseal Ltd. Thornccliffe Park, Chapeltown, Sheffield. S35 2YP
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk www.ronseal.co.uk

RONSEAL AND RONSEAL DOES EXACTLY WHAT IT SAYS ON THE TIN ARE REGISTERED TRADEMARKS OF THE SHERWIN-WILLIAMS COMPANY. © 2010. MADE IN UK.

600g e

