

**DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

**Ronseal Promise, if you do exactly what it says on the tin,  
this product will do exactly what it says on the tin.**

## **Ronseal One Coat Radiator Paint is heat resistant, long lasting and provides a super smooth enamel finish.**

**USAGE AREAS** • Primed, factory finished and previously painted radiators.

**PREPARATION** • Radiators should be switched off and cold. • Surfaces should be clean, dry and free from dust, dirt, grease or loose material. • Lightly abrade the surface and remove dust.<sup>\*</sup> • Avoid inhalation of dust, wear a suitable face mask when sanding. • Allow 24 hours before switching the radiator back on after painting.

**APPLICATION** • Stir well before and during use. • Apply with a bristle brush. • A second coat may be required where a major colour change is involved.

**COVERAGE AND DRY TIMES** • 8m<sup>2</sup> per litre. • Touch dry in 3 hours. • Overcoat after 16 hours if required. • Low temperature, high humidity or poor ventilation may extend drying and recoat times.

**CLEAN UP** • Remove as much product as possible from brushes prior to cleaning. • Clean brushes with brush cleaner or white spirit.

**CARE AND MAINTENANCE** • Clean surfaces with a detergent solution. • Avoid abrasive cleaners.

<sup>\*</sup> Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Ronseal Technical Services.



**Super Smooth  
Dry in 3 Hours**



**Resists Heat  
& Yellowing**



**One Coat  
No Primer Required**

### **RONSEAL ONE COAT RADIATOR PAINT**

Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed seek medical advice immediately and show this container label. Use only in well ventilated areas. Dispose of this material and it's container to hazardous or special waste collection point. Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction.

**WISE PRECAUTIONS** Always read the instructions carefully before use. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal or dispensing of waste coatings. To avoid the risk of spillage always store and transport in a secure and upright position.

EU limit value for this product (cat. A/i):  
600g/l (2007) / 500g/l (2010).  
This product contains a maximum of 480g/l VOC.



**For further advice please contact:**

Ronseal Technical Services  
Tel: 0114 240 9469  
Ronseal Ltd, Chapelton,  
Sheffield, S35 2YP.  
Tel: 0114 246 7171  
Fax: 0114 245 5629  
enquiry@ronseal.co.uk  
[www.ronseal.co.uk](http://www.ronseal.co.uk)

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company.  
© Ronseal 2010

**750ml e**