

**DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

**Ronseal Promise, if you do exactly what it says on the tin,  
this product will do exactly what it says on the tin.**

## Ronseal Multi-Surface Primer is formulated to prime and seal most household surfaces, providing superb adhesion and preventing peeling of the topcoat.

**USAGE AREAS** • Ideal for use on Tiles, Melamine, MDF, Plywood, Chipboard, Wood, Metal, uPVC, Plaster and Brick.  
• Not recommended for tiled floors, work tops or exterior surfaces.

**PREPARATION** • Surfaces should be clean, dry and free from dust, dirt and grease. **Tiled Surfaces:** Clean tiles thoroughly with a cleaner containing bleach. Clean grout lines with a nail brush if mould is present. Wipe down with a lint free cloth. Repair any damaged grout prior to priming. **Bare Wood:** Sand smooth and wipe clean.

**Bare Metal:** Sand with a fine grade wet and dry abrasive paper and wipe clean (galvanised metal should not be sanded). **Plasterboard:** Ensure that the surface is clean, firmly attached and dry. **New Plaster:** Allow plaster to dry thoroughly for at least 2 weeks. Fill any cracks or holes. Sand to remove any imperfections and remove dust with a damp sponge. **Previously Painted Surfaces:** Sand down and wipe clean with white spirit to remove dust. Spot prime bare areas prior to a full coat of primer. • Avoid inhalation of dust, wear a suitable face mask when sanding.

**APPLICATION** • Stir well. Apply with a synthetic filament brush. • Allow the primer to dry thoroughly before lightly sanding down any imperfections. • Dust clean with a dry cloth prior to the application of a topcoat.

**COVERAGE AND DRY TIMES** • 15m<sup>2</sup> per litre • Touch dry in 30 minutes • Overcoat after 4 hours. • Low temperature, high humidity or poor ventilation may extend drying and recoat times.

**CLEAN UP** • Remove as much product as possible from application equipment prior to cleaning. • Wash out brushes with water and detergent.



**Quick Drying  
Overcoat in 4 hours**



**Primes and seals most  
household surfaces**



**One Coat  
Tough, waterproof  
and durable**

**For further advice please contact:**

Ronseal Technical Services Tel: 0114 240 9469  
Ronseal Ltd. Chapeltown, Sheffield, S35 2YP.  
Tel: 0114 246 7171 Fax: 0114 245 5629  
enquiry@ronseal.co.uk  
[www.ronseal.co.uk](http://www.ronseal.co.uk)

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company.  
© Ronseal 2010

### **RONSEAL ONE COAT MULTI-SURFACE PRIMER**

Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, wash immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. Wear suitable gloves. Use only in well ventilated areas.

### **WISE PRECAUTIONS**

Always read the instructions carefully before use. Wear suitable clothing and protective gloves. Do not apply if air or surface temperatures are below 10°C (50°F). To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat. A/d):  
150g/l (2007) / 130g/l (2010).  
This product contains a maximum of 45g/l VOC.



**750ml**  