

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

Ronseal One Coat Tile Paint transforms tiled surfaces creating a super smooth and long lasting finish.

USAGE • Ideal for tiled areas around sinks, baths and cookers.
• Ideal for domestic shower areas. • Not recommended for floor tiles or tiled work surfaces. • For use on interior surfaces only.

PREPARATION • Surfaces should be clean dry and free from dust, dirt and grease. • Clean tiles thoroughly with a cleaner containing bleach. • Clean grout lines with a nail brush if mould is present. • Wipe down with a lint free cloth.
• Repair any damaged grout prior to decoration.

APPLICATION • Stir well. Apply with a bristle brush.
• Brush over the tiled area working into grout lines.
• Finish each tile in a vertical direction. • A second coat may be required where a major colour change is involved, or where tiles are heavily patterned. Allow 16 hours between coats. • Redefine grout lines after 24 hours using Ronseal One Coat Grout Pen.

COVERAGE AND DRY TIMES • 8m² per litre. • Touch dry in 1-2 hours. • Overcoat after 16 hours if required. • Low temperature, high humidity or poor ventilation may extend drying and recoat times.

CLEAN UP • Remove as much product as possible from application equipment prior to cleaning. • Clean brushes with brush cleaner or white spirit.

CARE AND MAINTENANCE • Clean surfaces with a detergent solution. • Avoid abrasive cleaners.

† This product contains fungicide for the purpose of preserving the coating against mould and fungal growth. * Avoid prolonged contact with water for 72 hours. Treated areas should be kept dry and free from humidity for 48 hours. During this period wipe off water/splashes immediately after use.



**Super Smooth
Dry in 1-2 Hours**



**Mould
Resistant†**



**One Coat
No Primer Required**

RONSEAL ONE COAT TILE PAINT

Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction. Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed seek medical advice immediately and show this container label. Use only in well ventilated areas. Dispose of this material and it's container to hazardous or special waste collection point.

WISE PRECAUTIONS Always read the instructions carefully before use. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal or dispensing of waste coatings. To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat. A/i):
600g/l (2007) / 500g/l (2010).

This product contains a maximum of 460g/l VOC.



For further advice please contact:

Ronseal Technical Services
Tel: 0114 240 9469
Ronseal Ltd. Chapelton,
Sheffield, S35 2YP.
Tel: 0114 246 7171
Fax: 0114 245 5629
enquiry@ronseal.co.uk
www.ronseal.co.uk

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company.
© Ronseal 2010

750ml e