

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™**

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

Ronseal One Coat Anti-Damp Paint is a high performance interior coating which permanently covers damp, water and common household stains.

USAGE AREAS • For interior walls or ceilings including plaster, cement and stone. • Not recommended for use on exterior surfaces, below ground level or where efflorescence is present. • Ronseal One Coat Anti-Damp Paint will not cure damp, all sources of damp should be eliminated prior to treatment. • Covers most household stains. • Can be over coated with standard emulsion paint.

PREPARATION • Surfaces should be clean, free from dust and loose material e.g. wallpaper, loose paint etc. • Mask any polystyrene or plastic surfaces before treatment. • Ensure the surface is not saturated. • If mould is present treat with a proprietary fungicidal wash. • Repair any holes, cracks and surface imperfections and sand down rough areas. • Allow any new plaster to dry for 7 days prior to application.

APPLICATION • Stir well before use. Do not thin. • Apply thoroughly by brush and approx. 30cm beyond affected area.

COVERAGE AND DRY TIMES • 5m² per litre depending on the texture and porosity of the surface being treated. • Touch dry in 1-2 hours. • Allow 4 hours before painting or wallpapering over. • In cold conditions dry times will be significantly extended.

CLEAN UP • Remove as much product as possible from application equipment prior to cleaning. • Clean brushes immediately after use in white spirit or brush cleaner. • Some local authorities have special facilities for disposing of waste coatings. • Do not empty product into drain or watercourses.



**One Coat.
Covers damp stains**



**Quick drying.
Decorate in 4 hours**



**Allows trapped
moisture to evaporate**

For further advice please contact:
Ronseal Technical Services Tel: 0114 240 9469
Ronseal Ltd. Chapelton, Sheffield, S35 2YP.
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk
www.ronseal.co.uk
Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company.
© Ronseal 2010

RONSEAL ONE COAT ANTI-DAMP PAINT

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed seek medical advice immediately and show this container label. Use only in well ventilated areas.

WISE PRECAUTIONS

Always read the instructions carefully before use. Wear suitable clothing and protective gloves. Ensure all sources of damp, including structural, plumbing faults and rising damp, are repaired prior to treatment. To avoid the risk of spilling always store and transport in a secure and upright position.

EU limit value for this product (cat. A/i):
600g/l (2007) / 500g/l (2010).
This product contains max 475g/l VOC



750ml e

