

# Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

## **Ronseal Outdoor Varnish**

The unique formulation of Ronseal Outdoor Varnish makes it the ultimate clear varnish for exterior use. It provides a long lasting finish which not only enhances the natural beauty of the wood grain but also protects it from water and UV damage.

Ronseal Outdoor Varnish is durable, long lasting, and has a flexible formula to help resist cracking, peeling and blistering. It also contains top quality UV light filters which protect wood from the sun's harmful rays, and being waterproof, will provide long lasting protection from water damage.

Usage Areas	Exterior doors, window frames, garden furniture and most exterior smooth planed timber.
Compatibility	Suitable for use on bare or varnished wood. Can also be used on already woodstained timber to provide added protection without darkening the effect.
Finish	Clear, rich, mellow finish.
No of coats	2 for treated wood, 3 for untreated wood.
Coverage	750ml will be sufficient to cover 10 sq m depending on the absorbency of the wood. Weathered wood may require more.
Dry Times	Allow 8 hours between coats.
Clean Up	Clean brushes with white spirit or paint brush cleaner.

## Preparation

Thorough preparation is the key to maximum performance. The durability of this product can be immaired by an unsound or poorly prepared surface. Bare wood: Make sure the wood is clean

and dry. Lightly sand to remove any loose wood fibres and wipe off any dirt, dust and grease with white spirit. Previously varnished or woodstained exterior wood: Sand to provide a key then wash with white spirit to remove any dirt, dust and grease. Any coating in a loose or poor condition should be removed. Previously painted surfaces must be completely stripped before application. For the best possible finish use a good quality brush.

#### Application

Stir well before and during use. Apply even coats and finish in the direction of the woodgrain. Apply a minimum of 3 coats to bare wood and 2 coats to previously varnished or woodstained exterior wood allowing 8 hours between coats. Do not apply in direct sunlight.

### Clean Up

Clean brushes with white spirit or paint brush cleaner. Remove as much varnish as possible from the brush before cleaning. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

## Important

Do not use on plastic type materials. Certain tropical woods, eg teak, iroko, etc, may prolong drying times and cause poor adhesion. Always test on a small area first. Always pay particular attention to completely covering the end grain. This product is lightly tinted and may have a darkening effect on light coloured bare wood.



#### Ronseal Outdoor Varnish

Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness and cracking. Keep out of reach of children. Avoid contact with keys, rince immediately with plenty of water and seek medical advice. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to hazardous or special waste collection point. Avoid release to the environment. Contains Cobalt 2. Ethylhexanoate, ETHVI. ME THYL KETOXIME, Neodecanoic acid, cobalt salt. May produce an alleroic reaction.

EU limit value for this product (cat. A/e): 500g/l (2007) / 400g/l (2010). This product contains max 400g/l VOC.



For further advice please contact: Ronseal Technical Services, Tel: 0114 240 9469 Ronseal Ltd., Chapeltown, Sheffield S35 2YP Tel: 0114 246 7171, Fax: 0114 245 5629 E-mail: enquiry@ronseal.co.uk www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010