

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

ADVANCED FORMULA

+

ULTIMATE APPLICATION

=

THE PERFECT FINISH

- Feeds and nourishes quality decks to prevent splitting and drying
- Translucent pigments enhance the colour of the deck whilst protecting it from the greying effects of UV rays
- Wax enriched formula waterproofs and protects the wood
- Durable formula resists scuffs and scratches caused by foot traffic

- Applies optimum film thickness to ensure ultimate protection
- Unique foam flock combination ensures a balanced and even application for a perfect finish
- Long flock fibres hold more oil than a brush for greater, smoother coverage.
- Thick foam pad base ensures Deck Pad moulds itself into all the grooves.
- Unique design also avoids pooling in grooves

Ronseal Perfect finish Decking Oil combines our advanced Ronseal Decking Oil with the Perfect Finish Decking Pad to provide the ultimate nourishing colour and protection. The Perfect Finish Deck Pad ensures the optimum film thickness is achieved with smooth, even coverage, delivering the ultimate protection and the Perfect Finish in one.

RONSEAL PERFECT FINISH DECKING OIL

Keep out of the reach of children. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas. Wear suitable gloves.

Wise precautions: To avoid risk of spillage, always store and transport in a secure and upright position. Protect from frost. Do not apply below 10°C or in high humidity. Contains alpha-3-(2-(2H-BENZOTRIAZOL...MIXTURE EC INDEX 607-176-00-3, bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Neodecanoic acid, cobalt salt. May produce and allergic reaction.

FOR FURTHER ADVICE PLEASE CONTACT:

RONSEAL TECHNICAL SERVICES,
Tel: 0114 240 9469
Ronseal Ltd. Thorncliffe Park,
Chapelton, Sheffield. S35 2YP
Tel: 0114 246 7171
Fax: 0114 245 5629
enquiry@ronseal.co.uk
www.ronseal.co.uk

RONSEAL AND RONSEAL DOES EXACTLY WHAT IT SAYS ON THE TIN ARE REGISTERED TRADEMARKS OF THE SHERWIN-WILLIAMS COMPANY © 2010. MADE IN UK

2.5 litre



Ronseal Perfect Finish Decking Oil is the next generation in decking oils enhancing the natural colour of the wood and delivering durable protection in an easy to use, quick drying, waterbased formulation. Ideal for quality decking the unique formula feeds and nourishes the wood replacing natural oils lost through weathering to resist cracking and splitting. The wax enriched formulation forms a protective barrier against water penetration protecting the deck from swelling and warping whilst the translucent colour pigments and added UV absorbers deliver long lasting protection against the greying effects of UV rays.

WHERE CAN IT BE USED? Ronseal Perfect Finish Decking Oil is specially formulated for use on all smooth or grooved decking timber including pre-treated, pressure treated and preservative impregnated wood. It is recommended for all exterior horizontal timber where foot traffic and wear will occur. It can be used on new wood, weathered wood, or wood which has been previously treated with Ronseal Perfect Finish Decking Oil. DUE TO ITS ADVANCED FORMULATION RONSEAL PERFECT FINISH DECKING OIL SHOULD NOT BE APPLIED IN CONJUNCTION WITH ANY OTHER DECKING OIL INCLUDING RONSEAL DECKING OIL. RONSEAL PERFECT FINISH DECKING OIL IS SUITABLE FOR TREATING PREVIOUSLY OILED DECKS, HOWEVER, BEFORE APPLICATION ENSURE THAT THE EXISTING FINISH HAS WEATHERED FOR AT LEAST 12 MONTHS AND THOROUGHLY CLEAN WITH RONSEAL DECKING CLEANER AND REVIVER OR RONSEAL DECKING RESTORER.

DRYING TIMES Rainproof in 2 hours. Re-coat in 4 hours. Drying times will vary depending on climatic conditions and substrate coated. Allow 24 hours before subjecting the coating to foot traffic.

COVERAGE This 2.5L pack is normally sufficient to coat 10-15 square metres with 2 coats for all board types. Coverage rates may vary depending on the absorbency and profile of the wood.

PREPARATION Only pre-treated, pressure treated or preservative impregnated timber should be used to build decking. Decking timber should be free from all dust, dirt, oil, mildew, algae and other contaminants. Remove any existing loose, flaking or peeling coatings. On pre-treated or wax coated decking timber try a small area for adhesion properties. New timber decks need to be thoroughly prepared before treatment. Apply Ronseal Decking Cleaner and scrub vigorously with a stiff brush to open the pores of the wood, this removes any contamination remaining from the manufacturing process. Rinse thoroughly with clean water, ideally using a pressure washer and allow to dry. Test the effectiveness of the cleaning by splashing the deck with water, if beading occurs, re-clean and retest prior to application. Shade label indicates approximate colour only. The treatment of a small test area to determine the final colour is recommended. Colour may be influenced by texture, grain, colour, porosity, type of wood and previous treatments.

APPLICATION Apply only to dry timber. Do not apply in wet conditions or when rain is likely before the product has time to dry.

1. Remove the overcap and assemble the pad. Remove the lid, which can be used as a tray if desired. If using the lid, wash with water and detergent and dry using a clean soft cloth. Stir the Oil thoroughly and then pour approximately 1 to 1.5cm into the tray. Do not dilute.

2. Dip the pad into the Oil, ensuring the underside of the pad is immersed. Dip the pad evenly taking care not to overload it.
3. Starting in the furthest corner, push or pull the pad in the direction of the woodgrain. The pad will hold more product than a brush so you will be able to apply in long, smooth strokes. The pad allows you to work away excess Oil and redistribute it evenly along the decking board, avoiding puddles in the grooves.
4. When applying to deck boards, treat 3-4 boards at a time to avoid overlap marks.
5. Two coats are recommended allowing 4 hours between coats.

A third coat may be applied if a deeper colour is required. For maximum protection apply to all sides and ends of the decking.

CLEAN UP & APPLICATOR CARE Remove as much decking Oil as possible from the pad and tray before cleaning. Clean pad and tray whilst wet with water and detergent. Always leave the pad to dry out with the flock facing upwards. Some authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.



EU limit value for this product
(cat A/i): 140 g/l (2007)/140g/l (2010).
This product contains max 50g/l VOC.