

**DOES  
EXACTLY  
WHAT IT  
SAYS ON  
THE TIN\***

## Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

### What is Ronseal Quick Drying Woodstain?

The unique formulation of Ronseal Quick Drying Woodstain is the ultimate all in one 'stain and finish', which provides an attractive long lasting finish. It not only enhances the natural beauty of the wood, but also protects it from water damage and the sun's harmful ultra-violet rays.

### Why Choose Ronseal?

- 1. Easy Preparation** No basecoats. No Primers. Ronseal Quick Drying Woodstain is all that is required to protect and decorate exterior wood. It is long lasting, not only beautifying but waterproofing and protecting your wood.
- 2. Easy Application** Unlike ordinary woodstains with Ronseal Quick Drying Woodstain you can now complete your exterior projects in less than a day. It is extremely easy to apply, it is touch dry in 30 minutes and can be recoated in 4 hours.
- 3. All Weather Protection** The water repellent formula keeps the wood dry by preventing excess water from entering the wood whilst allowing moisture inside the wood to evaporate. This helps prevent cracking, peeling and blistering.
- 4. Wash Brushes Out in Water** Ronseal Quick Drying Woodstain out-performs conventional woodstains, repelling water to protect your wood, yet providing the added benefit of being able to wash your brushes out in water.
- 5. Low Odour** Ronseal Quick Drying Woodstain has a low offensive odour.

**Preparation:** Make sure wood is clean and dry. Lightly sand to remove any loose wood fibres and wipe off any dirt, dust and grease with white spirit. Previously stained or weathered wood should be thoroughly sanded, then washed with white spirit and allowed to dry. Avoid inhalation of dust, wear a suitable face mask when sanding. Other finishes such as varnish or paint must

be completely removed before application. For the best possible finish use a good quality brush designed for the application of water-based finishes. Shade label indicates approximate colour only. Always test for colour on a small inconspicuous area.

**Application:** Stir well before and during use. Apply even coats finishing in the direction of the wood grain. Apply 3 coats allowing 4 hours between coats. Lightly sand before final coat. In warm and dry conditions, for best results dilute the first coat with up to 25% water. Do not apply in direct sunlight. Weathered wood may reduce coverage rate. Coverage varies with the absorbency of the wood. Remove as much product as possible from application equipment before cleaning. Clean brushes immediately with detergent and water. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal of waste coatings.

**Maintenance:** Once applied, Ronseal Quick Drying Woodstain can be easily maintained by applying one further coat every 3 years. On certain softwoods and horizontal or very exposed surfaces more frequent treatment may be necessary.

<b>Usage Areas:</b>	All smooth planed exterior timber – Doors, window frames, conservatories, cladding & garden furniture etc. Not suitable for decking.
<b>Compatibility:</b>	Suitable for use on bare wood or previously stained wood.
<b>Finish:</b>	Available in both gloss & satin finishes.
<b>Coverage:</b>	Up to 20 square metres per litre. 750ml sufficient for 12-15 square metres per coat.
<b>Dry Times:</b>	Touch dry in 30 minutes. Recoat in 4 hours.
<b>Clean Up:</b>	Brushes wash out in water and detergent.

**IMPORTANT:** Special precautions should be taken during surface preparation of pre 1960's painted surfaces over wood and metal as they may contain harmful lead. For further information please contact Ronseal Technical Services. To avoid the risk of spillage always store and transport in a secure and upright position.

### RONSEAL QUICK DRYING WOODSTAIN

Use only in well ventilated areas. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Keep out of reach of children. Protect from frost – do not apply at temperatures below 10°C or in high humidity.

EU limit value for this product (cat A/e): 150g/l (2007)/ 130g/l (2010).  
This product contains max 78g/l VOC.

### For further advice please contact:

Ronseal Technical Services,  
Tel: 0114 240 9469

Ronseal Ltd, Thorncliffe Park,  
Chapelton, Sheffield.  
S35 2YP

Tel: 0114 246 7171  
Fax: 0114 245 5629  
enquiry@ronseal.co.uk  
www.ronseal.co.uk



# 750ml e

Ronseal and Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams company. ©2010 Made in Great Britain.