

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.

Ronseal Stay White Radiator Paint is a superior heat resistant enamel finish which provides long lasting protection for radiators.

USAGE AREAS • Primed, factory finished and previously painted radiators and heating pipes.
• Not suitable for use on storage heaters.

PREPARATION • Radiators should be switched off and cold. • It is not recommended to apply this product in damp conditions or if temperature is below 10°C. • Surfaces should be clean, dry and free from dust, dirt, grease or loose material.
• Lightly abrade the surface and remove dust.*
• Avoid inhalation of dust, wear a suitable face mask when sanding. • Allow 24 hours before switching the radiator back on after painting.

APPLICATION • Stir well before and during use.
• Apply with a synthetic brush. • For best results apply two coats.

COVERAGE AND DRY TIMES • 15m² per litre.
• Touch dry in 30 minutes. • Overcoat after 6 hours. • Low temperature, high humidity or poor ventilation may extend drying and recoat times.

CLEAN UP • Remove as much product as possible from brushes prior to cleaning.
• Wash out brushes with water.

CARE AND MAINTENANCE • Clean surfaces with a detergent solution. • Avoid abrasive cleaners.

* Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.
For further advice contact Ronseal Technical Services.



**Resists knocks,
scratches & chipping**



**No primer
required**



**Touch dry
in 30 mins**

RONSEAL STAY WHITE RADIATOR PAINT

Use only in well ventilated areas. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Keep out of reach of children.

WISE PRECAUTIONS

Always read the instructions carefully before use. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal or dispensing of waste coatings. To avoid the risk of spillage always store and transport in a secure and upright position.



**For further advice
please contact:**

Ronseal Technical Services

Tel: 0114 240 9469

Ronseal Ltd. Chapeltown,
Sheffield, S35 2YP.

Tel: 0114 246 7171

Fax: 0114 245 5629

enquiry@ronseal.co.uk

www.ronseal.co.uk

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company. © Ronseal 2010

750ml e

EU limit value for this product (cat. A/i): 140g/l (2007) / 140g/l (2010).
This product contains a maximum of 75g/l VOC.

