

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN*

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

Ronseal Ultra Tough Hardglaze

Ronseal Ultra Tough Hardglaze is a superior polyurethane gloss varnish which protects interior wood whilst adding depth to the beauty of the wood grain. The polyurethane - alkyd formulation provides long lasting protection against knocks and scratches and resists most household chemical spillages including boiling water and alcohol. The high content of polyurethane in the varnish ensures quicker hardness and abrasion build up than other solvent based varnishes. The extended working time eliminates lap marks to deliver a rich, clear, mellow finish that enhances the beauty of the wood.

Usage Areas	Any bare or previously treated interior wood including doors, furniture, shelving, skirting boards, cork, hardboard or chipboard.
Compatibility	Suitable for use on bare wood or over existing solvent based finishes such as varnish or wood dye.
Finish	Rich, gloss sheen.
Number of coats	2 for treated wood, 3 for untreated wood.
Coverage	1 litre will be sufficient to treat 5 door sides with 2 coats (approx 10 sq m).
Dry Times	Touch dry in 2 hours. Recoat in 4 hours.
Clean Up	Clean brushes with white spirit or paint brush cleaner.

Preparation

Ensure all surfaces are free from wax, grease and oil by wiping with a cloth dampened with white spirit. Barewood: Sand smooth with fine sandpaper. Remove dust with a cloth dampened with white spirit. Varnished wood: Remove unsound varnish. Sand well to a uniform appearance and clean with white spirit. Allow to dry thoroughly. Avoid inhaling dust when sanding by wearing a suitable face mask.

Application

Stir well before and during use. Apply in a warm, well-ventilated room. Using a brush, apply 2 or 3 coats. Brush out evenly and finish each coat in the direction of the grain. Leave 4 hours between coats. Before final coat, lightly rub down using fine sandpaper and wipe with white spirit.

Clean Up

Clean brushes with white spirit or paint brush cleaner. Remove as much varnish as possible from the brush before cleaning. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

Important

Do not use on plastic type materials. Certain tropical woods may prolong drying times or cause poor adhesion. Always test on a small area first. Polyurethane varnishes may darken the colour of bare wood and dyed wood. Special precautions should be taken during surface preparations of pre-1960s paint surfaces over wood and metal as they contain harmful lead. Drying times may be extended when using over Colron Wood Dye. To avoid risk of spillage, always store and transport in a secure and upright position. For a water clear finish use Ronseal Quick Drying Clear Varnish. For use only as directed.

Ronseal Ultra Tough Varnish

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Keep away from sources of ignition – No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to a hazardous or special waste collection point. Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction.

EU limit value for this product (cat. A/e): 500g/l (2007) / 400g/l (2010). This product contains max 500g/l VOC.

For further advice please contact:

Ronseal Technical Services,

Tel: 0114 240 9469

Ronseal Ltd., Chapelton,
Sheffield S35 2YP

Tel: 0114 246 7171, Fax: 0114 245 5629

E-mail: enquiry@ronseal.co.uk

www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2010

750ml e 

1 LITRE ROUND (WELDED)

C.F.

R

C.B.

SILVER OF
TIN + 10%
SPOT WHITE

33% FREE
GET 1 LITRE FOR THE PRICE OF 750ml

RONSEAL
Does exactly what it says on the tin

**ULTRA TOUGH
MATTCOAT**
TOUGH POLYURETHANE MATT VARNISH
FOR INTERIOR WOOD

**CLEAR
VARNISH**

**RONSEAL'S HARDEST
PU VARNISH**

- Ultra tough polyurethane (PU) formulation for doors, windows and joinery
- Quicker hardness build up than other PU varnishes
- Resists most household chemicals and boiling water
- Extended working time eliminates lap marks
- Rich finish adds depth to the beauty of the wood grain

33% FREE
GET 1 LITRE FOR THE PRICE OF 750ml

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

Ronseal Ultra Tough Mattcoat

Ronseal Ultra Tough Mattcoat is a superior polyurethane matt varnish which protects interior wood whilst adding depth to the beauty of the wood grain. The polyurethane - alkylid formulation provides long lasting protection against knocks and scratches and resists most household chemical spillages including boiling water and alcohol. The high content of polyurethane in the varnish ensures quicker hardness and abrasion build up than other solvent based varnishes. The extended working time eliminates lap marks to deliver a rich, clear, mellow finish that enhances the beauty of the wood.

Usage Areas	Any bare or previously treated interior wood including doors, furniture, shelving, skirting boards, cork, hardboard or chipboard.
Compatibility	Suitable for use on bare wood or over existing solvent based finishes such as varnish or wood dye.
Finish	Rich, matt sheen.
Number of coats	2 for treated wood, 3 for untreated wood.
Coverage	1 litre will be sufficient to treat 5 door sides with 2 coats (approx. 10 sq m).
Dry Times	Touch dry in 2 hours. Recoat in 4 hours.
Clean Up	Clean brushes with white spirit or paint brush cleaner.

Preparation

Ensure all surfaces are free from wax, grease and oil by wiping with a cloth dampened with white spirit. Barewood: Sand smooth with fine sandpaper. Remove dust with a cloth dampened with white spirit. Varnished wood: Remove unsound varnish. Sand well to a uniform appearance and clean with white spirit. Allow to dry thoroughly. Avoid inhaling dust when sanding by wearing a suitable face mask.

Application

Stir well before and during use. Apply in a warm, well-ventilated room. Using a brush, apply 2 or 3 coats. Brush out evenly and finish each coat in the direction of the grain. Leave 4 hours between coats. Before final coat, lightly rub down using fine sandpaper and wipe with white spirit.

Clean Up

Clean brushes with white spirit or paint brush cleaner. Remove as much varnish as possible from the brush before cleaning. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

Important

Do not use on plastic type materials. Certain tropical woods may prolong drying times or cause poor adhesion. Always test on a small area first. Polyurethane varnishes may darken the colour of bare wood and dyed wood. Special precautions should be taken during surface preparations of pre-1950s paint surfaces over wood and metal as they contain harmful lead. Drying times may be extended when using over Calton Wood Dye. To avoid risk of spillage, always store and transport in a secure and upright position. For a water clear finish use Ronseal Quick Drying Clear Varnish. For use only as directed.

1 Litre e

Ronseal Ultra Tough Varnish

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to a hazardous or special waste collection point. Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction.

EU limit value for this product (cat. A+): 500g/l (2007) / 400g/l (2010). This product contains max 500g/l VOC.

For further advice please contact:
Ronseal Technical Services,
Tel: 0114 240 9469
Ronseal Ltd., Chapelton,
Sheffield S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk

www.ronseal.co.uk
Ronseal and Ronseal Does Exactly What It Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2009



CODE

1 LITRE ROUND (WELDED)

C.F.

R

C.B.

SILVER OF
TIN + 10%
SPOT WHITE

33% FREE
GET 1 LITRE FOR THE PRICE OF 750ml

RONSEAL
Does exactly what it says on the tin

**ULTRA TOUGH
SATINCOAT**
TOUGH POLYURETHANE SATIN VARNISH
FOR INTERIOR WOOD

**CLEAR
VARNISH**

**RONSEAL'S HARDEST
PU VARNISH**

- Ultra tough polyurethane (PU) formulation for doors, windows and joinery
- Quicker hardness build up than other PU varnishes
- Resists most household chemicals and boiling water
- Extended working time eliminates lap marks
- Rich finish adds depth to the beauty of the wood grain

33% FREE
GET 1 LITRE FOR THE PRICE OF 750ml

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

Ronseal Ultra Tough Satincoat

Ronseal Ultra Tough Satincoat is a superior polyurethane satin varnish which protects interior wood whilst adding depth to the beauty of the wood grain. The polyurethane - alkylid formulation provides long lasting protection against knocks and scratches and resists most household chemical spillages including boiling water and alcohol. The high content of polyurethane in the varnish ensures quicker hardness and abrasion build up than other solvent based varnishes. The extended working time eliminates lap marks to deliver a rich, clear, mellow finish that enhances the beauty of the wood.

Usage Areas	Any bare or previously treated interior wood including doors, furniture, shelving, skirting boards, cork, hardboard or chipboard.
Compatibility	Suitable for use on bare wood or over existing solvent based finishes such as varnish or wood dye.
Finish	Rich, satin sheen.
Number of coats	2 for treated wood, 3 for untreated wood.
Coverage	1 litre will be sufficient to treat 5 door sides with 2 coats (approx. 10 sq m).
Dry Times	Touch dry in 2 hours. Recoat in 4 hours.
Clean Up	Clean brushes with white spirit or paint brush cleaner.

Preparation

Ensure all surfaces are free from wax, grease and oil by wiping with a cloth dampened with white spirit. Barewood: Sand smooth with fine sandpaper. Remove dust with a cloth dampened with white spirit. Varnished wood: Remove unsound varnish. Sand well to a uniform appearance and clean with white spirit. Allow to dry thoroughly. Avoid inhaling dust when sanding by wearing a suitable face mask.

Application

Stir well before and during use. Apply in a warm, well-ventilated room. Using a brush, apply 2 or 3 coats. Brush out evenly and finish each coat in the direction of the grain. Leave 4 hours between coats. Before final coat, lightly rub down using fine sandpaper and wipe with white spirit.

Clean Up

Clean brushes with white spirit or paint brush cleaner. Remove as much varnish as possible from the brush before cleaning. Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

Important

Do not use on plastic type materials. Certain tropical woods may prolong drying times or cause poor adhesion. Always test on a small area first. Polyurethane varnishes may darken the colour of bare wood and dyed wood. Special precautions should be taken during surface preparations of pre-1950s paint surfaces over wood and metal as they contain harmful lead. Drying times may be extended when using over Calton Wood Dye. To avoid risk of spillage, always store and transport in a secure and upright position. For a water clear finish use Ronseal Quick Drying Clear Varnish. For use only as directed.

1 Litre e 

Ronseal Ultra Tough Varnish

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to a hazardous or special waste collection point. Contains Cobalt 2-Ethylhexanoate, ETHYL METHYL KETOXIME. May produce an allergic reaction.

EU limit value for this product (cat. A+): 500g/l (2007) / 400g/l (2010). This product contains max 500g/l VOC.

For further advice please contact:
Ronseal Technical Services,
Tel: 0114 240 9469
Ronseal Ltd., Chapelton,
Sheffield S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk

www.ronseal.co.uk

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2009



CODE