

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™**

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

Ronseal Wet Rot Wood Hardener is a liquid product designed to soak deep into the fibres of decayed wood. When dry the special resins harden, strengthening and reinforcing the softened wood forming a good solid base for wood filler as well as sealing against further moisture penetration.

- Soaks deep into softened and decayed wood.
- Strengthens, reinforces and seals soft and decayed wood.
- Provides a solid base for Wood Filler.
- Maximises the life of a wet rot repair job.
- Dries in 2 hours to allow a major job to be completed quickly.
- Cost-effective, long-term alternative to replacing joinery affected by wet rot.
- For interior or exterior use.

Ronseal High Performance Wood Filler is ideal for use with **Wet Rot Wood Hardener**.

USAGE AREAS

Can be used on any softened, decayed or rotting wood inside or outside the house. DO NOT use Ronseal Wet Rot Wood Hardener as a surface treatment or primer.

PREPARATION

Remove any completely decayed or very soft crumbly wood until a fairly sound base is exposed. The wood should be reasonably dry, free from grease, oil, dust and loose particles.

APPLICATION

1. Shake can before use.
2. Decant into lid then apply using a paint brush to the softened wood. Completely saturate the whole area to ensure full absorption.

NOTE: By drilling small holes into the damaged area you can achieve an even deeper hardening of decayed wood.

3. Allow to dry for 2 hours and remove any excess Hardener with a wire brush.
4. Use a good quality wood filler to finish. Ronseal Wet Rot Wood Hardener is the ideal base for Ronseal High Performance Wood Filler.
5. Prior to painting or staining sand off any remaining hardener.

CLEAN UP

Replace lid tightly. Clean brushes with cellulose thinners.

PRECAUTIONS


Avoid contact with glass, metal, plastics and painted surfaces.



Highly Flammable

Ronseal Wet Rot Wood Hardener

Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness or dizziness. Keep away from children. Keep away from sources of ignition - no smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with water and seek medical advice. Wear suitable gloves. If swallowed, seek medical attention immediately and show this container label. Use only in well ventilated areas. To avoid the risk of spillage, always store and transport in a secure and upright container.



For further
advice please
contact: Ronseal
Technical Services,
Tel: 0114 240 9469

Ronseal Ltd. Thorncliffe Park,
Chapeltown, Sheffield. S35 2YP
Tel: 0114 246 7171 Fax: 0114 245 5629
enquiry@ronseal.co.uk www.ronseal.co.uk

