

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™**

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

RONSEAL ANTI-BACTERIAL WORKTOP OIL with Silver guard technology harnesses the anti-bacterial qualities of Silver in a formulation ideal for enhancing and maintaining hardwood worktops. The slow release formulation delivers long lasting anti-bacterial protection killing E Coli and MRSA on contact and making it ideal for use in food preparation areas. The highly water resistant formula protects worktops from the damaging effects of water, penetrating deep into the wood to feed and nourish helping worktops to resist splitting and cracking. The high quality oil enhances the natural beauty of the hardwood leaving a clear soft sheen finish.

COVERAGE: 10-25 square metres dependent on the species of hardwood.

PREPARATION: Previously treated worktops: Ensure worktop surface is clean, dry and in good condition. **New or untreated worktops:** It may be necessary to lightly sand the surface of the worktop remove any loose wood fibres. Avoid inhalation of dust, wear a suitable face mask when sanding. Further sanding may be required if the wood is heavily stained or discoloured in places. Do not use steel wool or metal brushes for sanding. Finally, before application wipe down the worktop with white spirit using a cloth to remove any grease, resin or wax which may affect performance. Allow to dry before applying Ronseal Anti-bacterial Worktop Oil.

APPLICATION: Shake tin thoroughly for at least one minute before use.

Ronseal Anti-bacterial Worktop Oil can be applied either by brush or cloth. The oil should be at room temperature before application. To achieve the best finish, apply several thin coats. Apply liberally using a soft, dry lint free cloth or soft paint brush. Work lightly into the wood grain. Leave for 10 minutes and then wipe off any excess oil using a clean, lint free cloth. Apply 3-4 coats, leaving 24 hours between coats.

MAINTAINANCE: To maintain waterproof and anti-bacterial protection it is recommended to recoat the worktop with one coat, twice a year or more frequently if required. The worktop needs a maintenance coat when water on the worktop surface smudges instead of forming beads of water or when the worktop has lost its sheen.

CLEAN UP: Wash brushes out in white spirit. Wash cloths out in warm, soapy water before disposal. Some local authorities have special facilities for disposing of waste products. Do not empty into drains or watercourses. Ensure container is fully re-sealed after use.

RONSEAL WORKTOP OIL

Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Use only in well-ventilated areas.

WISE PRECAUTIONS

Whilst building up layers of oil, take care not to stain the worktop. Final colour will depend on the colour and porosity of the wood. Always try a test area prior to application.

For further advice please contact:

Ronseal Technical Services

Tel: 0114 240 9469

Ronseal Ltd. Chapeltown, Sheffield, S35 2YP.

Tel: 0114 246 7171 Fax: 0114 245 5629

enquiry@ronseal.co.uk www.ronseal.co.uk

Made in Great Britain. Ronseal & Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams Company. © Ronseal 2010



C00031

EU limit value for this product (cat. A/I):
140g/l (2007) / 140g/l (2010).
This product contains a maximum of 20g/l VOC.

1 Litre e



5 010214 862245 >