

DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN™

Ronseal Promise, if you do exactly what it says on the tin, this product will do exactly what it says on the tin.

Ronseal Yacht Varnish

Ronseal Yacht Varnish is a quality exterior varnish, available in either a gloss or satin finish that provides greater durability and superior protection than ordinary exterior varnishes. It contains a flexible resin that allows the varnish to move with the wood as it expands and contracts, so helping to prevent cracking, peeling and blistering. This unique formula is also highly water repellent to keep your wood drier.

Preparation

Ensure the wood is clean and dry. All varnish in loose or poor condition should be removed.

Bare wood: Sand to remove any loose wood fibres and wipe away any dirt, dust and grease with white spirit. **Varnished exterior wood:** Sand thoroughly to provide a key, then wash with white spirit to remove any dirt, dust and grease.

Application

Stir well before and during use. Using a brush, apply 2 or 3 coats. Brush out evenly and finish each coat in the direction of the grain. Leave 6 hours between coats. Before final coat, lightly rub down using fine sandpaper and wipe with white spirit.

Clean Up

Clean brushes with white spirit or paint brush cleaner. Remove as much varnish as possible from the brush before cleaning. Some local authorities have special facilities for disposal of waste coatings. Do not empty into drains or watercourses.

Important

Special precautions should be taken during surface preparation of pre-1960's painted surfaces over wood and metal as they may contain harmful lead. Do not use on plastic type materials. Certain tropical wood surfaces (teak, iroko, etc) may create longer drying times and poor adhesion. If in doubt, always test on a small area first. Always pay particular attention to completely covering the end grain, as an estimated 70% of moisture enters via this route. Do not use on areas previously treated with woodstains or paints. Instead use Ronseal Quick Drying Woodstain. Ronseal Yacht Varnish dries to a rich, mellow finish which may darken lighter woods. Test on a small area first.

Usage Areas	It has been specially formulated for external, smooth planed wood. For interior wood use Ronseal Quick Drying Varnish or Ronseal Diamond Hard Varnish.
Compatibility	Suitable for use on bare wood or over existing solvent based finishes such as varnish.
Finish	Available in both Gloss and Satin.
Number of Coats	Three coats are required. For previously treated surfaces, two coats should be adequate.
Coverage	Up to 16 square metres per litre. 1.25 litre will be sufficient to treat 5 door sides with 2 coats (20 sqm).
Dry Times	Touch dry in 4 hours, recoat in 6 hours. If more than 24 hours elapse, lightly sand to provide a key before overcoating.
Clean Up	Remove as much product from the brushes as possible and clean using white spirit.

RONSEAL YACHT VARNISH

Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeat exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from sources of ignition – No Smoking. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to hazardous or special waste collection point. Contains Cobalt 2-Ethylhexanote, ETHYL, METHYL KETOXIME. May produce an allergic reaction.

EU limit value for this product
(cat. A/e): 500g/l (2007) /
400g/l (2010). This product
contains max 480g/l VOC

For further advice please
contact: Ronseal Technical
Services, Tel: 0114 240 9469
Ronseal Ltd., Chapeltown,
Sheffield S35 2YP
Tel: 0114 246 7171, Fax: 0114 245 5629
E-mail: enquiry@ronseal.co.uk
www.ronseal.co.uk

Ronseal and Ronseal Does
Exactly What It Says on the
Tin are registered trademarks
of The Sherwin-Williams
Company, © 2010



1 Litre

